

## Sew a Hanging Sleeve After the Quilt is Bound

1 Cut or piece together fabric to make a strip 9" tall and the same width as the quilt.

2 Fold under short edges 1/4", wrong sides together. Fold under again. Press. Sew a straight or zigzag seam to hem the folds.



Fold sides and sew.

3 Now fold the strip lengthwise, wrong sides together, aligning its raw edges. Sew together with a 1/2" seam allowance. Press the seam allowance open.



Sew lengthwise, wrong sides together. Press seam open.

4 Place the open seam against the quilt's back. Center and pin the top edge of the tube to the back of the quilt, about 1/2" below the binding.

5 Use a [whipstitch](#) to sew the top edge of the tube to the quilt backing. Stitch into the batting occasionally to help strengthen the seam.



After sewing to quilt, sleeve will pooch out to allow space for rod.

6 Smooth the sleeve downward along the quilt back, then make a 1/2" fold along its length to create a pleat. Leaving the pleat intact, pin the sleeve bottom to the quilt.

7 Whipstitch the lower edge of the sleeve to the quilt. Remove pins. The sleeve will pooch out a bit to allow space for a hanging rod.

8 Whipstitch the back sides of the sleeve to the quilt. Leave the front sides unsewn to allow for rod insertion.